# SQBNCONNECTOR

Shunt-less Squib Connector. Connector for air-bag with Go/No-Go system, which allows locking connector and detect incomplete mating.

# Squib connector

#### **■** Features

# ●Shunt-Less Squib Connector

Mate with retainer without shorting bar.

#### ●Go / No-Go Mating System

Self-rejection system to prevent incomplete mating. Operation efficiency is improved by audible and tactile feeling of CPA clicking.

#### Stability of Electrical Connection

Terminal has three contact points.

Prevent the deformation of contact area by covering ferrule to contact spring.

### ●Noise Suppression

Ferrite core provides simple and reliable noise suppression characteristics.

# **■** Specifications

◆Current rating
★Withstanding voltage
★Temperature range
★3 A AC, DC max.
★1,000 VAC /minute
★1,000 VAC /minute
★2,000 VAC /minute

(including temperature rise in applying

electrical current)

•Insulation resistance : 100  $M\Omega$  min.


Applicable wire : AVSS 0.3 mm², 0.5 mm²

<sup>\*</sup>Compliant with ELV/RoHS2.

<sup>\*</sup>Contact JST for details.

# **SQBN** CONNECTOR

# Female terminal




	Applicable wire size		
Model No.	Conductor (mm²)	Insulation O.D. (mm)	Q'ty/reel
SSQBN-A03GJ-P	0.3 to 0.5	1.4 to 1.6	8,000

Material and Finish

Copper alloy, Nickel-undercoated, Contact area; gold-plated Barrel area; tin-plated

# Female housing assembly



## **Keying figure**









W code

X code

Y code

Z code


Circuits	Model No.	Keying figure	Housing color	Q'ty/box
	SQBNRB-02-1A-PK	W code	Pink	4,000
2	SQBNRB-02-1B-DV	X code	Purple	4,000
	SQBNRB-02-1C-H	Y code	Gray	4,000
	SQBNRB-02-1D-M	Z code	Green	4,000

# Material and Finish

Female Housing: Glass-filled PBT CPA: Glass-filled PBT, Orange Spring cover: Glass-filled PA, Natural Spring: SUS

Note: Contact JST for details.

# Front cover



Circ	uits	Model No.	Housing color	Q'ty/box
2	2 S	QBNFL-02H-1A-Y	Yellow	6,000


Material and Finish

Glass-filled PBT

Note: Contact JST for details.

# **SQBN** CONNECTOR

# Rear cover




Circuits	Model No.	Housing Color	Q'ty/box
2	SQBNRL-02H-1A-Y	Yellow	18,000

#### Material and Finish

PB<sup>-</sup>


Note: Contact JST for details.

# Ferrite



Circuits	Model No.	Q'ty/box
2	SQBNF-02-1A	5,600

# Retainer



### Keying figure









W code

X code

Y code

Z code

Circuits	Model No.	Keying figure	Housing color	Q'ty/box
	SQBP-02H-1A-PK	W code	Pink	15,000
2	SQBP-02H-1B-DV	X code	Purple	15,000
	SQBP-02H-1C-H	Y code	Gray	15,000
	SQBP-02H-1D-M	Z code	Green	15,000

Material and Finish

Glass-filled PA

Note: Contact JST for details.

# Crimping machine, Applicator

Strip terminal	Crimping	Crimp applicator MKS-L	
Strip terrilinal	machine	Dies	Crimp applicator with dies
SSQBN-A03GJ-P	AP-K2N	MK/SSQBN-A03-P	APLMK SSQBN-A03-P

Note: 1. Contact JST for details.

<sup>2.</sup> When crimping operation is conducted using an applicator and die set other than the above, JST cannot guarantee the performance of the terminal.