



This button terminal is used as a contact interface for lamp sockets and fuse holders in automobiles. Products using this contact are far more reliable and easier to use than conventional products that use solder connections.

Shape A	Shape B	Shape C
4.4	6.3	6.3 8.0

	Applicable wire					014.1		
Model No.	mm²	AWG #	Insulation O.D. (mm)	Shape	Finish	Q'ty / reel		
SBT-31-001		20 to 18	2.1 to 3.0	А	-	7,500		
SBT-31T-001					Tin-plated			
SBT-31-002				в	-	10,000		
SBT-31T-002					Tin-plated (reflow treatment)			
SBT-31-003				с	-			
SBT-31T-003					Tin-plated			
Material								

Brass

Note: The SBT-31(T)-003 has a dent at the end to increase the area that contacts the mating fuse. The SBT-31(T)-002 does not have such a dent.

Crimping machine, Applicator-

Contact	Crimping machine	Crimp applicator	Dies	Crimp applicator with dies
SBT-31(T)-001	AP-K2N	MKS-L	MK/SBT-31-001	APLMK SBT31-001
SBT-31(T)-002 SBT-31(T)-003		MKS-L	MK/SBT-31-002	APLMK SBT31-002

* Compliant with RoHS.

- * Refer to "General Instruction and Notice when using Terminals and Connectors" at the end of this catalog.
- * Contact JST for details.

RoHS compliance